


TP6/D

CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS WITH DELRIN TOOTHED DISCS NOT TO MARK LEADS

20.OL11 STANDARD

20.OL12 REINFORCED



Minimum cutting length "B" = 4,6mm and maximum lead "d" = 0,8mm

TP6/97


CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS WITH QUICK SET UP



20.OL01 /97 STANDARD

20.OL04 /97 REINFORCED

20.OL06 /97 REDUCED




This system automatically adjusts the bending wheels, reducing the set-up time and making it easier.

This system is available with the some versions of the TP6 machine. Warning= the maximum pitch possible with the /97 system is 40 mm and the maximum "B" is 10 mm

STANDARD VERSIONS OF TP6, TP6/D AND TP6/97 MACHINES

20.OL01 - 20.OL11 - 20.OL01/97


TP6/1 STANDARD VERSION



	MM		IN	
	min	max	min	max
P	6,5	60	.255	2.362
B	4	13	.157	.511
c	1,2		.047	
L		50		1.968
d	0,4	1,2	.015	.047
D	0,4	16	.015	.629

20.OL04 - 20.OL12 - 20.OL04/97


TP6/4 EXTRA REINFORCED BENDING



	MM		IN	
	min	max	min	max
P	10,16	60	.4	2.362
B	5	13	.196	.511
c	2,4		.094	
L		50		1.968
d	0,6	1,4	.023	.055
D	0,6	16	.023	.629

20.OL06 - 20.OL06/97


TP6/6 REDUCED BENDING – ADJUSTABLE PITCH



	MM		IN	
	min	max	min	max
P	5,08	60	.2	2.362
B	4	13	.157	.511
c	0,8		.031	
L		50		1.968
d	0,4	0,8	.015	.031
D	0,4	10	.015	.039

20.OL07 - 20.OL09 - 20.OL10

TP6/7 – TP6/9 – TP6/10 REDUCED BENDING FIX PITCH



	MM		IN	
	min	max	min	max
B	4	10	.157	.393
c	0,5		.019	
d	0,4	0,6	.015	.023
D	0,4	4	.015	.157

code 20.OL07	P	5,08	.2
code 20.OL09	P	7,62	.3
code 20.OL10	P	10,16	.4

TP6 OPTIONAL ACCESSORIES




BR6 - 400200 REEL HOLDER




MOT98 - 7915030 - 220 V. -MOTOR DRIVE UNIT
MOT98 - 7915031 - 110 V - MOTOR DRIVE UNIT.



TNS - 21.0011 WASTE TAPE EJECTOR



CS10 - 51.0100 FEEDER FOR LOOSE COMPONENTS



200240 BODY GUIDE

MAX LEGHT COMPONENT BODY = 45 MM
