



# TP6/PR-F/1 CUTTING BENDING FORMING MACHINE FOR AXIAL COMPONENTS



---

43.OLO1 STANDARD

---




The model TP6/PR-F is designed for cutting and forming axial taped components. Version 43.OLO1 is suitable for lead  $\varnothing$  0,5 to 0,9 mm (.19 to .035"). Die assemblies designed for each one of the version, need to be ordered separately depending on the form required. It is possible to order special forms, supplying Olamef with drawings and specifications. This high quality machine is designed and manufactured to last long time. Preforming operations are realized in order not to mark, scratch or deform leads. Machine's adjustment takes advantage of '97 system. It can be motorised. Waste tape ejector TNS is always already included with the machine's price.

---

PRODUCTION/HOUR  
TAPED: 7000  
LOOSE: 5000


---



TNS - 21.0013 WASTE TAPE EJECTOR IS  
ALWAYS ALREADY INCLUDED WITH THE MACHINE


# TP6/PR-F/1 STANDARD DIE ASSEMBLIES

## 420800 - STAND OFF 2,5MM




	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	2.4
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	6	9	.236	.354
<b>B</b>	8	11	.314	.433
<b>d</b>	0,5	0,9	.019	.035
<b>D</b>	0,5	8	.019	.314
<b>z</b>	2	4	.078	.157

## 420850 - LOCK IN




	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	2.4
<b>L</b>		50		1.023
<b>c</b>	1,2		.047	
<b>h</b>	4,5	8	.177	.314
<b>B</b>	7,5	11	.295	.433
<b>d</b>	0,5	0,8	.019	.031
<b>D</b>	0,5	8	.019	.314
<b>z</b>	3	4	.118	.157

## 420900 - REDUCED PITCH




	MM		IN	
	min	max	min	max
<b>P</b>	7,62	58,42	.3	2.3
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	5	9	.196	.354
<b>B</b>	7	11	.275	.433
<b>d</b>	0,5	0,9	.019	.035
<b>D</b>	0,5	8	.019	.314
<b>z</b>	2	4	.078	.157
<b>E</b>	1,27		.05	

## 420950 - LOCK IN BIG HOLES




	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	2.4
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	4,5	8	.177	.314
<b>B</b>	7,5	11	.295	.433
<b>d</b>	0,6	0,9	.023	.035
<b>D</b>	0,6	8	.023	.314
<b>z</b>	3	4,5	.118	.177

## 420750 - STAND OFF 3MM




	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	2.4
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	6,5	9,5	.255	.374
<b>B</b>	8,5	11,5	.334	.452
<b>d</b>	0,5	0,9	.019	.035
<b>D</b>	0,5	8	.019	.314
<b>z</b>	2	4	.078	.157

## 421000 - BODY LOCKED




	MM		IN	
	min	max	min	max
<b>P</b>	10,16	60,96	.4	2.4
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	5	8	.196	.314
<b>d</b>	0,5	0,6	.019	.023
<b>D</b>	2	8	.078	.314

## 420650 - "U" BEND



	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	1.2
<b>L</b>		50		1.968
<b>c</b>	1,2		.047	
<b>h</b>	6	12	.236	.472
<b>B</b>	6	12	.236	.472
<b>d</b>	0,5	0,9	.019	.035
<b>D</b>	0,5	8	.019	.314


## 42100004 - LOW BODY LOCKED



	MM		IN	
	min	max	min	max
<b>P</b>	10.16	60.96	.4	2.4
<b>L</b>		50		1.023
<b>c</b>	1,2		.047	
<b>h</b>		8		.314
<b>B</b>		11		.433
<b>d</b>	0,5	0,8	.019	.031
<b>D</b>	0,5	8	.019	.314
<b>z</b>	3	4	.118	.157

# TP6/PR-F OPTIONAL ACCESSORIES

---




BR6 - 400200 REEL HOLDER

---




MOT98/A - 7915032 - 220 V. - MOTOR DRIVE UNIT  
MOT98/A - 7915033 - 110 V. - MOTOR DRIVE UNIT

---



CS40 - 51.0400 FEEDER FOR LOOSE COMPONENTS

---



430240 BODY GUIDE

---