


TP6/PR-F/3

CUTTING BENDING
FORMING MACHINE FOR
AXIAL COMPONENTS




43.0L03 EXTRA REINFORCED



The model TP6/PR-F/3 is designed for cutting and forming axial taped components. Version 43.0L03 is suitable for lead \varnothing 1 to 1,3mm (.039 to .051"). Die assemblies designed for each one of the version, need to be ordered separately depending on the form required. It is possible to order special forms, supplying Olamef with drawings and specifications. This high quality machine is designed and manufactured to last long time. Preforming operations are realized in order not to mark, scratch or deform leads. It can be motorised. Waste tape ejector TNS is always already included with the machine's price..


PRODUCTION/HOUR
TAPED: 7000
LOOSE: 5000



TNS - 21.0013 WASTE TAPE EJECTOR IS
ALWAYS ALREADY INCLUDED WITH THE MACHINE


TP6/PR-F/3 STANDARD DIE ASSEMBLIES

430700 - STAND OFF 3MM




	MM		IN	
	min	max	min	max
P	12.7	60.96	.5	2.4
L		50		1.968
c	2,5		.098	
h	11	16	.433	.629
B	13	18	.511	.708
d	1	1,3	.039	.051
D	1	8	.039	.314
z	2	4	.078	.157

430900 - REDUCED PITCH




	MM		IN	
	min	max	min	max
P	10,16	58,42	.4	2.3
L		50		1.968
c	2,5		.098	
h	9	16	.354	.629
B	11	18	.433	.708
d	1	1,3	.039	.051
D	1	8	.039	.314
z	2	4	.078	.157
E	1,27		.05	

420650 - "U" BENDING



	MM		IN	
	min	max	min	max
P	12.7	60.96	.5	2.4
L		50		1.968
c	2,5		.098	
B	13	18	.511	.708
d	1	1,3	.039	.051
D	1	8	.039	.314


TP6/PR-F OPTIONAL ACCESSORIES




BR6 - 400200 REEL HOLDER



MOT98/A - 7915032 - 220 V. - MOTOR DRIVE UNIT
MOT98/A - 7915033 - 110 V. - MOTOR DRIVE UNIT



CS40 - 51.0400 FEEDER FOR LOOSE COMPONENTS



430240 BODY GUIDE
